radaway 🔲	KN-02F
CUSTOMER DATA:	MOUNTING PROFILE: X Y COMPLIES WITH SERIES AND MODELS
SERIES AND MODEL: INSTALLER DATA:	
FITTINGS COLOR:	
GLASS COLOR:	OTHER:
MEASUREMENT METHODS: ENTRANCE:	SIDE,,X" SIDE,,Y"
X Y X Y AKG AKP AKG	X Y X Y IKP
MAIN DRAWING	CONSTRUCTION HEIGHT AT "0" POINT:
₽…₩	STANDARD OTHER:
	MEASURE AND GIVE DEVIATIONS (A BLANK FIELD MEANS NO DEVIATION)
	DL DW DR
X DW DR	
	CHOOSE THE VARIANT OF THE LAYOUT OF THE BUILDING WALLS FOR X AND
Y	*X
	X X X Y X Y X Y X X X X X X X X X X X X
*	GIVE DIMENSIONS AND METHOD OF INTERPRETATION:
A ** W	X Y Y S1 S2
	53
*INDICATE "0" POINT(S) AND SEPCIFY DEVIATION(S) AS A NEGATIVE VALUE	
POINT(S) "0" IS/ARE THE HIGHEST POINT(S) ON THE FLOOR / SHOWER TRAY / L-SHAPE WAL ** CHECK THE FLATNESS AND DESCRIBE ANY CURVES. STANDARD GAP IS 3 MM, CONSIDER IN	L S4 CREASING IT.

ATTENTION, RADAWAY, FOR TECHNOLOGICAL REASONS, RESERVES THE POSSIBILITY OF MAKING CONSTRUCTION CHANGES.

REMARKS: -