







CUSTOMER DATA: \_\_\_\_\_  
 SERIES AND MODEL: \_\_\_\_\_ INSTALLER DATA: \_\_\_\_\_  
 FITTINGS COLOR: \_\_\_\_\_  
 GLASS COLOR: \_\_\_\_\_

MEASUREMENT METHODS:



MOUNTING PROFILE:

COMPLIES WITH SERIES AND MODELS

OTHER:

R

☐

☐

MAIN DRAWING

CONSTRUCTION HEIGHT AT "0" POINT:


STANDARD




OTHER: .....

MEASURE AND GIVE DEVIATIONS: (A BLANK FIELD MEANS NO DEVIATION)

DR




DW




CHOOSE THE VARIANT OF THE LAYOUT OF THE BUILDING WALLS FOR X:

X ☐




X ☐



\* DIMENSIONS ACCORDING TO THE MAIN DRAWING

X ☐



GIVE DIMENSIONS AND METHOD OF INTERPRETATION:

	X
S1	
S2	
S3	

\* INDICATE "0" POINT(S) AND SPECIFY DEVIATION(S) AS A NEGATIVE VALUE  
 POINT(S) "0" IS/ARE THE HIGHEST POINT(S) ON THE FLOOR / SHOWER TRAY / L-SHAPE WALL

\*\* CHECK THE FLATNESS AND DESCRIBE ANY CURVES. STANDARD GAP IS 3 MM, CONSIDER INCREASING IT.

 ATTENTION, RADAWAY, FOR TECHNOLOGICAL REASONS, RESERVES THE POSSIBILITY OF MAKING CONSTRUCTION CHANGES.

REMARKS: